

DWELLSCAPE™

VELOCITY 7 X 48 PLANK



SPECIFICATIONS

INSTALLATION TYPE:	Glue Down
INSTALLATION LOCATION:	On, Above, or Below Ground
RADIANT HEAT:	Compatible with Radiant Heat
THICKNESS:	2mm
WEAR LAYER:	0.15mm (6mil)
PLANK SIZE:	7" Wide X 48" Long
TEXTURE:	Embossed Wood Pattern
EDGE PROFILE:	Square Edge
SQ FT PER CARTON:	51.33 Sq Ft (37.03 lbs)

PRODUCT FEATURES AND BENEFITS

- CeramaSHIELD™** Antimicrobial finish up to 3 Times more durable than the competition
- Products do not contain formaldehyde or ortho phthalates or heavy metals
- Waterproof moisture protection
- Easily replace damaged planks/tiles
- Limited 10yrs Residential & 5yrs Limited Commercial Warranty

*See warranty and care and maintenance

PERFORMANCE SPECIFICATIONS

Reaction to Fire	EN 13501-1+A1	Bfl-S1
Emission of Formaldehyde	EN 717-1	Class E1
Impact Sound Transmission	ASTM E492-09	IIC 56 (concrete slab with drop ceiling)
Flammability (Critical Radiant Flux)	ASTM E648-17a	Class I - 1.00 Watts/cm2
Flexibility	ASTM F137-08	No Breaks or Cracks
Dimensional Stability (after exposure to heat)	ASTM F2199	(-) 0.007" Length, (-) 0.006" Width
Static Load Limit (conducted at 1000 lb)	ASTM F970-17	Residual Indentation: 0.005"
Static Coefficient of Friction	ASTM D2047-11	0.80
Light Stability (after 400 hours)	ASTM F1515-15	1.00Δ Delta E
Chemical Resistance	ASTM F925	No Change
Heat Stability	ASTM F1514-03	1.22Δ Delta E
Size & Squareness	ASTM F2421-05	Pass

